



12.1" Rimless LCD Monitor



Features

1. Rimless front bezel with Protective Glass.
2. Sleek modern style throughout product appearance.
3. Spill & Dustproof meet IP54 requirement (Front).
4. Multiple Video Signals available with System combinations.
5. Multi-Touch PCAP touch (option).
6. Low power consumption with LED backlight.
7. Meet VESA 75x75 mm Wall-Mount standard.
8. Designed with cable management.
9. Robust base stand match touch operating.

Specification

Model	P121MG / P121MP
Cabinet Color	Black
Front Panel	Mitsubishi PMMA Hardness > 5H (JIS D0202), T > 93% (P121MG) Projected capacitive touch (P121MP)
Display Type	12.1" diagonal TFT active matrix with LED backlight
Recommended Resolution	800 x 600 / Support 1024 x 768 @60Hz
Brightness	500 cd/m ² (Typ.)
Contrast Ratio	700:1 (Typ.)
Viewing Angle	160° (H) / 140° (V)
I/O Connectivity	D-Sub 15pin VGA. HDMI. DC12V (P121MG) D-Sub 15pin VGA. HDMI. DC12V. Mini USB (P121MP)
Backlight MTBF	50,000 hrs (Min.)

* Specification is subject to change without prior notice.


Application

Supermarket / Chain stores / Hospitality /
Factory automation




I/O indication

P121MG



P121MP



Dimension (unit: mm)

