



8" Rimless LCD Monitor



Features

1. Rimless front bezel design.
2. Integrated with protection glass (Model: P080VG) or 5 wires resistive flat touch (Model: P080VR) or PCAP touch (Model: P080VP)
3. VESA 75 x 75 mm wall mounting standard
4. Low power consumption only 6W with LED backlight
5. Sleek surface throughout monitor's appearance
6. Optional with stability enhanced pole base
7. Tilting angle adjustment up to 68°
8. User friendly OSD control buttons
9. Support 1024x768 @60Hz
10. Smart cable management
11. Small footprint

Specification

Model	P080VG / P080VR / P080VP
Cabinet Color	Black or White (By MOQ)
Front Panel	Mitsubishi PMMA Hardness > 5H (JIS D0202), T > 93% (P080VG) 5 wires resistive flat touch (P080VR) / PCAP touch (P080VP)
Display Type	8" diagonal TFT active matrix with LED backlight
Resolution	800 x 600 support 1024 x 768 @60Hz
Panel Brightness	250 cd/m ² (Typ.)
Contrast Ratio	500:1 (Typ.)
Viewing Angle	140° (H) / 120° (V)
I/O Connectivity	D-Sub 15 pins
Backlight MTBF	20,000 hrs (Min.)

* Specification is subject to change without prior notice.


Applications:

Supermarket/Chain stores/Hospitality/
Factory automation




I/O indication

P080VG



P080VR/P080VP



Dimension (unit: mm)

