



# 12.1" Rimless LCD Monitor



## Features

1. Rimless front bezel design, spill & dust proof, Plastic rear cover
2. Low power consumption only 4W with LED backlight
3. Sleek surface throughout monitor's appearance
4. VESA 75 x 75 mm wall mounting standard
5. User friendly control buttons
6. Integrated protection glass (**P121UG**)
7. 5 wires Resistive touch (**P121UR**)
8. Project capacitive touch Panel (**P121UP**)
9. Cabinet designed to fit variety USB accessories
10. Smart cable management

## Application

Supermarket / Chain stores / Hospitality  
/ QSR Factory automation




## Specification

Model	P121UG / P121UR / P121UP
Cabinet Color	Black or White (by MOQ)
Front panel	Mitsubishi PMMA Hardness > 5H (JIS D0202), T > 93% ( <b>P121UG</b> ) 5 wires Resistive touch ( <b>P121UR</b> ) Projected capacitive touch Panel ( <b>P121UP</b> )
Display Type	12.1" diagonal TFT active matrix with LED backlight
Recommended Resolution	800 x 600
Panel Brightness	500 cd/m <sup>2</sup> (typ.)
Contrast Ratio	700:1 (typ.)
Viewing Angle	160° (H) / 140° (V)
I/O Connectivity	Mini USB x 1
Backlight MTBF	50,000 hrs (min.)

\* Specification is subject to change without prior notice.

## I/O indication

### P121UG/UR/UP



## Dimension (unit: mm)

