



# 12.1" Rimless LCD Monitor



### Features

1. Rimless front bezel with Protective Glass.
2. Sleek modern style throughout product appearance.
3. Spill & Dustproof meet IP54 requirement (Front).
4. Multiple Video Signals available with System combinations.
5. Multi-Touch PCAP touch (option).
6. Low power consumption with LED backlight.
7. Meet VESA 75x75 mm Wall-Mount standard.
8. Designed with cable management.
9. Robust base stand match touch operating.

### Specification

Model	P121VG / P121VP
Cabinet Color	Black
Front Panel	Mitsubishi PMMA Hardness > 5H (JIS D0202), T > 93% (P121VG) Projected capacitive touch (P121VP)
Display Type	12.1" diagonal TFT active matrix with LED backlight
Recommended Resolution	800 x 600 / Support 1024 x 768 @60Hz
Panel Brightness	500 cd/m <sup>2</sup> (Typ.)
Contrast Ratio	700:1 (Typ.)
Viewing Angle	160° (H) / 140° (V)
I/O Connectivity	D-Sub 15pin VGA. DC12V (P121VG) D-Sub 15pin VGA. DC12V. Mini USB (P121VP)
Backlight MTBF	50,000 hrs (Min.)

\* Specification is subject to change without prior notice.


### Application

Supermarket / Chain stores / Hospitality /  
Factory automation




### I/O indication

#### P121VG



#### P121VP



### Dimension (unit: mm)

