



Apis Series  
**P150VG**  
**P150VR**  
**P150VP**



## 15" Rimless LCD Monitor



New Capacitive Touch keys control design provide high durability of operation, also with a thin & whole flat front panel gives an elegant and compact appearance.

### Features

1. Rimless front bezel design, spill & dust proof
2. Low power consumption only 10W with LED backlight
3. Sleek surface throughout monitor's appearance
4. VESA 75 x 75 mm wall mounting standard
5. User friendly OSD control buttons
6. Integrated protection glass (P150VG)
  - 5 wires resistive flat touch (P150VR)
  - PCAP touch (P150VP)
7. Smart cable management
8. Small footprint

### Specification

Model	P150VG / P150VR / P150VP
Cabinet Color	Black or White ( By MOQ )
Front Panel	Mitsubishi PMMA Hardness > 5H (JIS D0202), T > 93% (P150VG) 5 wires resistive flat touch (P150VR) PCAP touch (P150VP)
Display Type	15" diagonal TFT active matrix with LED backlight
Resolution	1024 x 768
Panel Brightness	350 cd/m <sup>2</sup> (Typ.)
Contrast Ratio	1000:1 (Typ.)
Viewing Angle	176° (H) / 176° (V)
I/O Connectivity	D-Sub 15pin, DC12V, Mini USB ( for P150VR/P150VP )
Backlight MTBF	50,000 hrs (Min.)

\* Specification is subject to change without prior notice.


### Application

Supermarket / Chain stores / Hospitality /  
 Factory automation




### I/O indication

#### P150VG



#### P150VR / P150VP



### Dimension (unit: mm)

