

## Rugged Industrial PC




### FEATURES

- ◆ USB-C Alt DP Mode with combined PD up to 60Watts.
- ◆ Rugged for industrial operations.
- ◆ Fanless for reliability and durability.
- ◆ Connects up to three display monitors.
- ◆ Multiple powered input/output ports to meet heavy industrial applications.
- ◆ Choose from Intel's Alder Lake N97 and N305 CPUs.


### Featured Connectors



### I/O Interfaces



### Dimensions



## Technical Specification

| Model                 |                       | PTNx  |
|-----------------------|-----------------------|---|
| CPU                   |                       | Intel Alder Lake <b>N97</b> (4-Core, 3.6GHz) /<br>Intel Alder Lake <b>Core-i3 N305</b> (8-Core, 3.8GHz) |
| System Memory         |                       | 1 * DD4, SO-DIMM (Max. 16GB)  |
| Graphic               |                       | Intel UHD Graphics, 1.2GHz  |
| Storage               | SSD                   | 1 * M.2 (Max. 512GB)  |
| External I/O Port     |                       | 6 * USB 3.0   |
|                       |                       | 1 * USB-C (Alternate DP Mode)   |
|                       |                       | 1 * USB-C (Alternate DP Mode w/o Audio)   |
|                       |                       | 2 * RS232 (RJ-50) Pin 9: Ring/5V/12V by BIOS  |
|                       |                       | 4 * RS232/RS422/RS485 (DB9)   |
|                       |                       | 1 * Remote Power Switch Connector   |
|                       |                       | 2 * HDMI  |
|                       |                       | 1 * LAN (RJ45, 2.5GbE Intel 226V)   |
|                       |                       | 1 * Audio (3.5mm, Mic/Spk Combo Jack)   |
|                       |                       | 1 * DC-In (5.5*2.5mm, Support 12~24VDC)   |
|                       |                       | 1 * CD/DIO (RJ12) 12V, or<br>Bypass DC-In 19V/24V by Jumper   |
|                       |                       | 1 * 3.5mm (Combo Jack)  |
|                       |                       | 1 * Power Rocker Switch   |
|                       |                       | Others  |
| Power                 |                       | External AC Power Adapter   |
| Environmental         | Operating Temperature | 0°C ~ 50°C  |
|                       | Storage Temperature   | -20°C ~ 85°C  |
|                       | Operating Humidity    | 5% ~ 90% RH non-condensing  |
|                       | Storage Humidity      | 5% ~ 90% RH non-condensing  |
| Housing               |                       | Aluminum, Metal   |
| OS Support            |                       | Windows® 10, 11, Linux 4.0 Kernel   |
| Dimension (W x D x H) |                       | 250 * 140 * 48.7 mm   |
| Weight (N.W./G.W.)    |                       | 1.94Kgs / 4.28Kgs   |
| Wall Mount            |                       | VESA 75x75 mm   |

\* Specification is subject to change without prior notice.