



Apis Series  
**P104MG**  
**P104MR**  
**P104MP**



## 10.4" Rimless LCD Monitor



New Capacitive Touch keys control design provide high durability of operation, also with a thin & whole flat front panel gives an elegant and compact appearance.

### Features

1. Rimless front bezel design, spill & dust proof, meets IP54 requirement
2. Low power consumption only 6W with LED backlight
3. Cable cover to prevent unexpected pull from users
4. Sleek surface throughout monitor's appearance
5. Viewing angle adjustment up to 68°
6. Universal power supply adaptor with changeable plug
7. VESA 75 x 75 mm wall mounting standard
8. User friendly OSD control buttons
9. Integrated protection glass (P104MG)
  - 5 wires Resistive touch panel (P104MR)
  - PCAP touch panel (P104MP)
10. Smart cable management
11. Support 1024 x 768 @60Hz
12. Optional with stability enhanced pole base

### Specification

Model	P104MG / P104MR / P104MP
Cabinet Color	Black or White (By MOQ)
Front Panel	Mitsubishi PMMA Hardness > 5H (JIS D0202), T > 93% (P104MG) 5 wires Resistive touch (P104MR) PCAP touch panel (P104MP)
Display Type	10.4" diagonal TFT active matrix with LED backlight
Recommended Resolution	800 x 600
Panel Brightness	300 cd/m <sup>2</sup> (Typ.)
Contrast Ratio	500:1 (Typ.)
Viewing Angle	150° (H) / 110° (V)
I/O Connectivity	VGA, HDMI, DC 12V (P104MG) VGA, HDMI, DC 12V, Mini USB (P104MR / P104MP)
Backlight MTBF	10,000 hrs (Min.)

\* Specification is subject to change without prior notice.


### Application

Supermarket / Chain stores / Hospitality /  
 Factory automation




### I/O indication

#### P104MG



#### P104MR/P104MP



### Dimension (unit: mm)

