



# 12.1" Rimless LCD Monitor



### Features

1. Rimless front bezel with Protective Glass.
2. Sleek modern style throughout product appearance.
3. Spill & Dustproof meet IP54 requirement (Front).
4. Multiple Video Signals available with System combinations.
5. Multi-Touch PCAP touch (option).
6. Low power consumption with LED backlight.
7. Meet VESA 75x75 mm Wall-Mount standard.
8. Designed with cable management.
9. Robust base stand match touch operating.

### Specification

| Model                  | P121MG / P121MP  |
|------------------------|--|
| Cabinet Color          | Black  |
| Front Panel            | Mitsubishi PMMA Hardness > 5H (JIS D0202), T > 93% (P121MG)<br>Projected capacitive touch (P121MP) |
| Display Type           | 12.1" diagonal TFT active matrix with LED backlight  |
| Recommended Resolution | 800 x 600 / Support 1024 x 768 @60Hz   |
| Panel Brightness       | 500 cd/m <sup>2</sup> (Typ.)   |
| Contrast Ratio         | 700:1 (Typ.)   |
| Viewing Angle          | 160° (H) / 140° (V)  |
| I/O Connectivity       | D-Sub 15pin VGA. HDMI. DC12V (P121MG)<br>D-Sub 15pin VGA. HDMI. DC12V. Mini USB (P121MP)           |
| Backlight MTBF         | 50,000 hrs (Min.)  |

\* Specification is subject to change without prior notice.


### Application

Supermarket / Chain stores / Hospitality /  
Factory automation




### I/O indication

#### P121MG



#### P121MP



### Dimension (unit: mm)

