

### **Features**

- 1. Rimless front bezel design, spill & dust proof, Plastic rear cover
- 2. Low power consumption only 10W with LED backlight
- 3. Sleek surface throughout monitor's appearance
- 4. Universal power brick with changeable plug
- 5. VESA 75 x 75 mm wall mounting standard
- 6. User friendly OSD control buttons
- 7. Integrated protection glass (P150MG)
- 8. 5 wires resistive flat touch (P150MR)
- 9. Projected capactive touch (P150MP)
- 10. Smart cable management
- 11. Small footprint

## **Specification**

| Model                  | P150MG / P150MR / P150MP   |
|------------------------|--|
| Cabinet Color          | Black  |
| Front Panel            | Mitsubishi PMMA Hardness > 5H (JIS D0202), T > 93% (P150MG)<br>5 wires resistive flat touch (P150MR)<br>Projected capactive touch (P150MP) |
| Display Type           | 15" diagonal TFT active matrix with LED backlight  |
| Recommended Resolution | 1024 x 768   |
| Panel Brightness       | 350 cd/m <sup>2</sup> (typ.)   |
| Contrast Ratio         | 800:1 (typ.)   |
| Viewing Angle          | 160° (H) / 150° (V)  |
| I/O Connectivity       | D-Sub 15pin VGA. HDMI. DC12V <b>(P150MG)</b><br>D-Sub 15pin VGA. HDMI. DC12V. Mini USB <b>(P150MR/P150MP)</b>                              |
| LED Backlight MTBF     | 50,000 hrs (Min.)  |

<sup>\*</sup> Specification is subject to change without prior notice.

# **Application**


Supermarket / Chain stores / Hospitality / Factory automation



#### I/O indication

# P150MG VGA in

## P150MR / P150MP



## Dimension (unit: mm)

