

## 21.5" Full Waterproof Panel PC

**Built Tough. Built to Perform.**



### FEATURES

- **IP67-rated** for superior waterproof and dustproof protection.
- Rugged **M12 waterproof I/O connectors** for reliable performance.
- **Stainless steel** + enclosure for maximum durability and hygiene.
- **Slim design** to allow seamless integration into tight or compact industrial environments.
- **Fanless design** for ultra-reliable and maintenance-free operation.
- Supports both **Resistive & PCAP** touch for versatile applications.
- **Multiple CPU** platform options to meet your performance needs.
- Built with **no mechanical component** for long lasting operation.
- **VESA 100x100mm** for easy pole, wall, or stand installation.


**Engineered to excel in the toughest environments,** our Waterproof Panel PC is the perfect solution for food & beverage production lines and industrial automation facilities.



**Superior waterproof** and dustproof protection.



**Stainless steel + Metal** enclosure for maximum durability and hygiene.




**Rugged M12 I/O connectors** for reliable performance.




**Fanless design** for ultra-reliable, maintenance-free operation.



Supports both **Resistive and PCAP** touch for versatile applications.



**Multiple CPU** platform options to meet your performance needs.



**Slim design** to allow seamless integration into tight or compact industrial environments.



**VESA mounting** compatibility for easy pole, wall, or stand installation.

## Product Views



Front View



Rear View



Side View




Top View



Bottom View

## Dimensions



## Technical Specification

Model		PPC215FP
CPU		Intel Elkhart Lake J6412 (4-Core, 2GHz)
System Memory		2 * DDR4, 3200 SO-DIMM (Max. 32GB)
Graphic		Intel Integrated Graphics
Storage	SSD	1 * SATA 2.5" (HDD/SSD Bay)
LCD	Size	21.5" TFT LCD
	Resolution	1920 * 1080
	Brightness	250 cd/m2 (Typ.)
	Contrast Ratio (Typ.)	1000:1
	Viewing Angles (H/V)	178° / 178°
	MTBF	50,000 hrs (Min.)
Touch Screen	Type	10-Points Projected Capacitive
External I/O Port		2 * USB 3.0, 2 * USB2.0
		1 * COM (RS-232/422/485)
		1 * HDMI
		2 * LAN (RJ45, Gigabit Ethernet)
		1 * LINE-OUT
		1 * DC-In (9V ~ 24V)
		1 * Power Button
Power		AC Power Adapter (12V/8A, 96W)
Environmental	Operating Temp.	0°C ~ 50°C
	Storage Temp.	-20°C ~ 80°C
	Operating Humidity	20% ~ 85% RH non-condensing
	Storage Humidity	20% ~ 85% RH non-condensing
Housing		Stainless Steel 304 + Metal SECC
OS Support		Windows® 10, 11
Dimension (W * H * D)		563 * 354 * 70 mm
Weight (N.W./G.W.)		10.5Kg / 13Kg
Wall Mount (VESA)		100*100mm

\* Specification is subject to change without prior notice.